



TEAIS FONPOL A, Two component polyurethane base for joinery and joinery products.

Descripción

Colourless two component fast dry primer. Suitable for wood with low porosity and application of open or close pore. Catalytic: F29/N11. Solvent: DISOLAIS.

Aplicación

Ideal for wooden protection both new and restored. Tapaporos is the suitable primer for all types of wood where a high quality decorative finish is required according with the properties and characteristics of the product.

Surface preparation

Must be quite clean, free of greases, wax, dust, loose particles and perfectly dry and flat.

Modes of application

Stir the content of the package properly before using.

- Before applying the product the admixture must be done at 50%, it means that for example we must mix 1 litre of A component with 1/2 litre of B component (TEAIS CATALIZADOR F29/ TEAIS CATALIZADOR N11).
- It can be applied with an aerographic gun, air- less, brush, roller, etc?

Clean up

With TEAIS CLEANING SOLVENT.

Data sheet

AspectViscous liquid

Colour/sYellowish



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



Density 0,99 kg/Lt +-0,05 ay 20 ° c

Mix proportion 2/1

Dry for repainting 4 hours

Dry upon touching 1 hour

Viscosity Admixture: 22 s CF n4

Performance

From 8 to 10 sqm/litre

Storage

2 years in their original packages, tightly closed, avoiding extrem temperatures, protected from the weather and in dry and open-air places.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email.: desarrollo@teais.es

síguenos en:

