

Ander B

antiskid chemical treatment for average requirements

Description:

Ander B est un traitement antidérapant chimique pour revêtement de sol à partir de substances actives qui produisent une microporosité sur le support.

Uses:

Moderate traffic areas which requires to avoid sliding. For indoor and outdoor pavements, in shower trays or nonplastic bathtubs. Ander B it's also used when you want to apply pavement paints on vitrified tiles, improving paint adhesion. Ander B can also be used as a previous step for the application of Ander F, when the application should be performed on vitrified holders to provide an adequate adherence for the treatment.



Surface preparation:

For the treatment application the surface must be clean and dry.

Application:

- Apply using a paint brush or broom onto the surface to be treated.
- Leave the product to act for 5 to 10 minutes.
- Rinse the surface with plenty of water.
- If a micro-texturisation is required, the treatment can be repeated once the surface becomes dry, it does this first application steps must be done again, spreading the product, letting it rest for an hour and finally remove it and drying the support properly.
- Precaution must be taken during the application, by protecting face and hands.
- Previous testing must be carried out so as to make sure that the product is suitable.
- The treatment changes the surface from shiny to matt.
- All surfaces in contact must be protected because it can cause stains.



- EASY APPLICATION
- EFFICIENT TREATMENT FOR SLIPPERY SURFACES
- IRREVERSIBLE
- MATTS VITRIFIED SURFACES
- ADDS MICROPOROSITY TO THE HOLDER

Packaging: 1l, 5l, 25l
Coverage: 5 or 6 sqm/litre depending the support.





ander-b

ANTISKID CHEMICAL TREATMENT FOR AVERAGE REQUIREMENTS

Edition: 2

03/2010

Technical department

Description:

Ander B is a chemical antiskid flooring treatment based on active substances that generate a microporosity in the holder.

Uses:

Moderate traffic areas which requires to avoid sliding. For indoor and outdoor pavements, in shower trays or non-plastic bathtubs. Ander B it's also used when you want to apply pavement paints on vitrified tiles, improving paint adhesion. Ander B can also be used as a previous step for the application of Ander F, when the application should be performed on vitrified holders to provide an adequate adherence for the treatment.

Technical features:

Aspect	colourless liquid
Density	1.16 kg/lt
Temperature of work	5 to 30°C

Features & benefits:

* EASY APPLICATION * EFFICIENT TREATMENT FOR SLIPPERY SURFACES * IRREVERSIBLE * MATTS VITRIFIED SURFACES * ADDS MICROPOROSITY TO THE HOLDER *

Surface preparation:

For the treatment application the surface must be clean and dry.

Clean up:

With plentiful clean water.

Coverage:

5 or 6 sqm/litre depending the support.

Application

- Apply using a paint brush or broom onto the surface to be treated.
- Leave the product to act for 5 to 10 minutes.
- Rinse the surface with plenty of water.
- If a micro-texturisation is required, the treatment can be repeated once the surface becomes dry, it does this first application steps must be done again, spreading the product, letting it rest for an hour and finally remove it and drying the support properly.
- Precaution must be taken during the application, by protecting face and hands.
- Previous testing must be carried out so as to make sure that the product is suitable.
- The treatment changes the surface from shiny to matt.
- All surfaces in contact must be protected because it can cause stains.

Packaging:

Available in packs of:

- 1 Litre
- 25 Litre

Storage:

1 year in their original packagings, protected from the weather, stored in a cool and dry place.

The information provided on this technical data sheet and particularly the recommendations for the application and use of the product is based on our current knowledge and are provided in good faith, considering that the products are used, handled and stored under normal conditions and within the limits of its useful life. The possible differences between the materials, supports, and real conditions in the application site can be so important that it is no possible to establish a warranty with this document or any other information provided. The user must verify with a suitability test that the product conforms to the required use. Users should refer to the information included in the last technical data sheet edition.



PROFESSIONAL CONSTRUCTIVE SOLUTIONS

©TEAIS S.A. - All rights reserved - Avda. da Enerxía, nº 153, Pol. Ind. de Sabón - 15143 Arteixo, A Coruña
Telf.: 981 602 111 - Fax: 981 601 508 - Email: comex@teais.es

